



BLACK GOLD DRILLING HOSE | LOW TEMP

HIGH PRESSURE OILFIELD HOSE



○	D	○	○	R	kg						
in.	mm	in.	mm	bar	psi	bar	psi	in.	mm	lb./ft.	kg/m
*3.0	76	4.61	117	345	5000	862	12500	48	1219	10.8	4.9
*3.5	89	5.25	133	345	5000	862	12500	54	1372	12.8	5.8
*4.0	102	5.61	142	345	5000	862	12500	54	1372	13.4	6.1
3.5	89	6.04	153	517	7500	1292	18750	54	1372	24	11
*4.0	102	6.48	168	517	7500	1292	18750	60	1524	26	12
4.0	102	6.69	170	517	7500	1290	18750	52	1320	29	13

APPLICATION

Gates Black Gold Low Temp hose product family is specifically designed to meet or exceed the severe demands of current drilling methods including directional drilling and high velocity pressure impulses in severe cold temperatures.

Tube: Type C3 (Modified Nitrile) | Black

CONSTRUCTION

Reinforcement: Multiple layers of textile fabric and steel cable

Cover: Type C4 (Modified Nitrile) Black

TEMPERATURE

-40°F to +180°F (-40°C to +82°C)

FSL RATING

FSL 1 | *FSL 2*

STANDARDS

API 7K

COUPLINGS

Swaged, Crimped or Bonded with a full range of fitting options including hammer unions, flanges, hubs, etc.

PACKAGING

Each assembly packaged in a heavy duty wooden crate for transport

OPTIONS

Accessories such as safety clamps, hose lift eyes, abrasion resistance wrap, and stainless steel armor are available upon request. Test Certificates and Certificates of Conformance are shipped with every order. Full data books and 3rd party witness tests are available for an additional fee.